

Head office

Pol. El Portazgo nave 62-B
50011 Zaragoza (Spain)
Tel. ++34 976259125
Fax ++34 976373775
E-mail: export@sonelco.com
www.sonelco.com

SONELCO 
sistemas de comunicación y sonido

SONELCO 

**HIFI-WIFI
SYSTEM**



WiFi SYSTEM

The best surround sound with Sonelco WiFi speakers. Power, HiFi sound, innovative design and maximum wireless functionality.

Ideal for homes, but also for business and other spaces where high audio performance is required.

To listen to music without limits. You can play audio from the cloud (through router) or directly from a local device (Smartphone, tablet, computer, etc.)

- ➔ High power stereo amplifier.
- ➔ 2-way coaxial speaker, with fiberglass woofer and high fidelity sound reproduction.
- ➔ Simple control of all sound functions from mobile, tablet or other device with WiFi, through APP.
- ➔ Aesthetic and functional design. With its compact design and innovative grid, together with its installation in false ceiling, the speaker integrate perfectly into any decoration. Ideal dimensions since the 6,5 " of the loudspeaker allow to obtain superior benefits in a space of only 21 cm.
- ➔ Easy installation and configuration



W-77

Amplified WiFi speaker: 20+20W.
It includes all features.

W-64

Auxiliary speaker: 80/160W.
Passive speaker to connect to amplified model.

W-20

Amplified speaker: 20+20W.
Amplified speaker to connect to model with WiFi in rooms with more than 2 speakers.

Section	Model	W-77	W-64	W-20
Wi-Fi	Standard	802.11b/g/n		
	Audio formats supported	MP3, AAC, WAV, FLAC, APE, OGG, WMA, DTS, AC3, m4a		
Amplifier	Power (RMS)	20+20 W		20+20 W
	Type	Stereo, built-in speaker box		Stereo, built-in speaker box
	Impedance	4 Ohm		4 Ohm
	Signal / Noise Ratio (dB)	≥ 100 dB		≥ 100 dB
	Frequency response (-3dB)	20-20000 Hz		20-20000 Hz
	Supply	230 V AC		230 V AC
Loudspeaker	Type	↔ 2 way coaxial ↔		
	Installation	↔ Flush-mount in false ceiling ↔		
	Colour	↔ White ↔		
	Grid	↔ Metallic grille with high degree of perforation and held with neodymium magnets ↔		
	Loudspeaker	↔ 6,5" woofer made of fiberglass and 0,8" tweeter ↔		
	Impedance	↔ 4 Ohm ↔		
	Power (Nominal / Maximum)	↔ 80/160 W ↔		
	Sound Pressure 1W, 1m	↔ 90 dB ↔		
	Frequency response	↔ 40-25000 Hz ↔		
	Dimensions (Diameter*Height)	↔ 210*135 mm ↔		
	Hole for flush-mounting (diameter)	↔ 180 mm ↔		
	Required depth for installation	↔ 135 mm ↔		
	Fixing	↔ Adjustable clamps ↔		

Installation examples:



Lounge in private home



Boutique

